

Pedestals KKT, KT – Basic technical specification



.mdd

MDD has a leading position among manufacturers of office furniture with many awards that prove quality and continuously increase demand for its products.

The realities of today's market require constant quality improvement at all levels of modern organization. This applies in particular to customer service, marketing, quality of products and also to quality of processes within the company.

Partnership relations among employees and with business partners form a base of economic growth and success of the company.

Constant investments in innovative machinery park, optimization of management systems and an expansion of production halls allow to minimize the lead times for the product of the highest quality.

More than twenty years of experience in office furniture industry come with reference from a long list of companies and institutions to show their appreciation for an efficient and comprehensive service.

MDD is highly aware of the environment.

Being located in the forest region with lake by its side, MDD takes the nature seriously and invests constantly in a modern and energy-efficient solutions to preserve the local life. Company puts emphasis on waste segregation and recycling. MDD has been awarded for the exceptional care and involvement in waste disposal. All materials used are environmentally friendly and enjoy a high 95 % rate of being recycled.



General informations:

Warranty:

MDD products – **5 years.**

Electrical components and fabric – **2 years.**

Certificate - MFC:



Assembly:

the product comes pre-assembled

Packing:

cardboard

Compliant with standards:

PN-EN 14073-2:2006

Boards density:


12 mm – 690 – 750 kg/m³

18 mm – 650 – 690 kg/m³

28 mm – 610 – 630 kg/m³

36 mm – 610 – 630 kg/m³


Mobile pedestal without handles



1. **Body** – MFC 18 mm, ABS edge
2. **Front** – MFC 18 mm, ABS edge
3. **MFC drawer** – roll runners, max load 25 kg, 80% extractio
4. **Sliding pencil tray** – MFC 18 mm
5. **Pencil tray** – plastic, colour: black
6. **Central lock** – foldable key
7. **Castors** – Ø50 mm, two with brakes
8. **Optional cushion SKP13** – for pedstal, max load 120 kg, ordered separately

ATTENTION – sitting on the pedestal possible only after mounting the cushion (SKP13); the pedestal with cushion is intended for sitting only
– moving the pedestal while sitting may result in damaging the castors


Mobile pedestals



1. **Top** – MFC 18 mm, ABS edge
2. **Body** – MFC 18 mm, ABS edge
3. **Front** – MFC 18 mm, ABS edge
4. **MFC drawer** – roll runners, max load 25 kg, 80% extractio
5. **Sliding pencil tray** – MFC 18 mm
6. **Pencil tray** – plastic, colour: black
7. **Suspension files drawer** – max load 30 kg, 100% extraction
8. **Central lock** – foldable key
9. **Castors** – Ø50 mm, two with brakes


ATTENTION – sitting on the pedestal possible only after mounting the cushion (SKP13); the pedestal with cushion is intended for sitting only
– moving the pedestal while sitting may result in damaging the castors

Stationary pedestals




1. **Top** – MFC 28 mm, ABS edge
2. **Body** – MFC 18 mm, ABS edge
3. **Front** – MFC 18 mm, ABS edge
4. **MFC drawer** – roll runners, max load 25 kg, 80% extractio
5. **Pencil tray** – plastic, colour: black
6. **Central lock** – foldable key
7. **Leveling** – 10 mm range


Pedestals with top overhang - dimensions (mm)



Mobile pedestal without handles *



KKT110
348 / 600 / 586
22 kg



KKT11
416 / 600 / 586
26 kg

Mobile pedestal *



KKT130
334 / 600 / 586
22 kg



KKT13
402 / 600 / 586
26 kg



KKT12
402 / 600 / 586
32 kg

Stationary pedestal *




KKT64
402 / 600 / 740
34 kg



KKT74
402 / 800 / 740
37 kg

Pedestal cushion *



SKP13
400 / 600 / 52
3 kg

* dimensions expressed in millimeters: width x depth x height

Pedestals KKT, KT Basic	Date of preparation 24.09.2020	The data contained in this document is valid in the day of its preparation. Change of the product, as long as it does not affect the basic features of it, does not require consistent updates of the document.	page 5/10
			products

Pedestals with top overhang 600 mm wide *



KT664
600 / 600 / 740
35 kg



KT674
600 / 800 / 740
39 kg

Pedestals with top overhang 800 mm wide *



KT864
800 / 600 / 740
37 kg



KT874
800 / 800 / 740
41.9 kg

Pedestals with top overhang 1000 mm wide *



KT1064
1000 / 600 / 740
38.9 kg



KT1074
1000 / 800 / 740
44.9 kg

Pedestals with top overhang 1200 mm wide *



KT1264
1200 / 600 / 740
41.4 kg




KT1274
1200 / 800 / 740
47.9 kg

* dimensions expressed in millimeters: width x depth x height

Top, front




Body, base, whole KKT11, KKT110



SKP13


Fabric Nemo



Technical data:

Material	polyester 100%
Fabric weight	366g/m2
Abrasion resistance rubs	PN-EN ISO 12947 - 2:2 100,000
Pilling resistance	scale 1-8, max. 8, PN-EN ISO 105 - B02 (3-4)
Colour fastness to rubbing	scale 1-5, max. 5, PN-EN 1021 - 2, PN-EN 1021 - 1
Colour fastness to rubbing	skscale 1-5, max. 5, EN ISO 105x12 (wet/dry) 4-5

Fabric Runner – second price group



Technical data:

Material	polyester 100%
Fabric weight	510 g/lm (16.45 oz/lin.yd.)
Abrasion resistance rubs	BS EN ISO 12947-2 70,000 Martindale cycles
Pilling resistance	scale 1-5, max 5, EN ISO 12945-2 (4-5)
Colour fastness to light	scale 1-8, max 8, EN ISO 105-B02 (5-7)
Colour fastness to rubbing	scale 1-5, max 5, EN ISO 105x12 (wet/dry) 4-5
Acoustic test sound absorption	ISO 354
Flammability	BS EN 1021-2 Match, CA TB 117-2013, BS EN 1021-1 (cigarette) Class Uno UNI 9175 Class 2, EMME

Fabric Medley – second group



Technical data:

Material	polyester 100%
Fabric weight	510 g/lm (16.45 oz/lin.yd.)
Abrasion resistance rubs	BS EN ISO 12947-2, 75,000 cykli Martindale
Pilling resistance	scale 1-5, max. 5, EN ISO 12945-2 (4)
Colour fastness to light	scale 1-8, max. 8, EN ISO 105-B02 (5-7)
Colour fastness to rubbing	scale 1-5, max. 5, EN ISO 105x12 (wet/dry (4-5/4-5))
Acoustic test sound absorption	ISO 354
Flammability	BS EN 1021-1 (cigarette) BS 476 Part 7, Class 2 Class Uno UNI 9174 – UNI 8457 CA TB 117-2013 ASTM E 84 Class I

Fabric Atlantic * – second price group



Technical data:

Material	polyester 100%
Fabric weight	530 g/lm (17.09 oz/lin.yd.)
Abrasion resistance rubs	BS EN ISO 12947-2, 110,000 Martindale cycles
Pilling resistance	scale 1-5, max. 5, EN ISO 12945-2 (4-5)
Colour fastness to light	scale 1-8, max. 8, EN ISO 105-B02 (5-7)
Colour fastness to rubbing	scale 1-5, max. 5, EN ISO 105x12 (wet/dry (4-5/4-5))
Flammability	CA TB 117-2013 ASTM E 84 Class I BS EN 1021-2 (match) BS EN 1021-1 (cigarette)

Fabric River – second group



Technical data:

Material	polyester 100%
Fabric weight	300g/m2 (+/- 5%)
Abrasion resistance rubs	100,000 Martindale cycles (EN ISO 12947-1,2)
Pilling resistance	EN ISO 12945-2 (5)
Colour fastness to light	4 (EN ISO 105-B02)
Colour fastness to rubbing	dry: 4-5, wet: 3 (EN ISO 105-x12)
Flammability	BS 5852: Part 1, Ignition Source 0 (cigarette) BS 5852: Part 1, Ignition Source 1 (match) EN1021 – 2

* There is a possibility of ordering the product in full colour spectrum of Atlantic range, as per Gabriel's pattern book, within 8 weeks

Fabric Xtreme – third price group



Technical data:

Material	100% Trevira Clame (CS) 100% Recykling (YS) Flame Retardant polyester. Non metallic dyestuffs.
Fabric weight	310 g/m2 ±5% (435g/lin.m ±5%)
Abrasion resistance rubs	60,000 Martindale cycles (CS) 100,000 Martindale cycles (YS)
Colour fastness to light	6 (ISO 105 – B02)
Colour fastness to rubbing	wet: 4, dry: 4 (ISO 105 – X12)
Flammability	EN 1021 – 1 (cigarette), EN 1021 – 2 (match) BS 7176 Low Hazard, NF P92-507 M1, DIN 4102 B1, UNI 9175 Class 1 IM, UNI 8456, UNI 9174 & UNI 9177 Classe Uno, ÖNORM B 3825 & A 3800-1 NF D 60-013

Fabric Synergy – third price group



Technical data:

Material	95% Virgin Wool , 5% Poliamid
Fabric weight	400g/m2 ±5% (560 g/lin.m ±5%)
Abrasion resistance rubs	Independently certified ≥100,000 Martindale cycles
Colour fastness to light	5 (ISO 105 – B02)
Colour fastness to rubbing	ISO 105 – X12 – wet: 4, dry: 4
Flammability	EN 1021 – 1 (cigarette), EN 1021 – 2 (match), BS 7176 Low Hazard, UNI 9175 Classe 1 IM, ÖNORM B 3825 & A 3800-1

Fabric Atlas – fourth price group



Technical data:

Material	90% new wool, 10% nylon
Fabric weight	286g/m2, 400g/lm
Abrasion resistance rubs	100,000 cykli Martindale, EN ISO 12947
Colour fastness to light	ISO 105 B02: 6-7
Colour fastness to rubbing	ISO 105-X12:2001, (wet/dry) 4-5/4-5
Flammability	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5 5852 Crib 5, BS 5852 ignition source 3, BS 5852 Part 1, NF D 60 013, UNI 9175 1IM, US Cal. Bull. 117-2013


Fabric Field2 – fourth price group




FD-463 Yellow



FD-963 Green



FD-123 Beige



FD-132 Grey



FD-142 Graphite



FD-662 Red



FD-673 Blue-red



FD-782 Navy blue



FD-693 Burgundy



FD-192 Black

Technical data:

Material	100% Trevira CS
Fabric weight	321g/m ² , 450g/lm
Abrasion resistance rubs	100,000 cykli Martindale, EN ISO 12947
Colour fastness to light	ISO 105 B02: 5-7
Flammability	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5 5852 Crib 5, DIN 4102 B1 FAR 25.853, UNI 9177 classe 1, US Cal. Bull. 117-2013